






## Product Data Sheet (2018-09-03)

### 28481 - Flexbalance hydraulic separator Plus 65F



Description	Flexbalance hydraulic separator Plus 65F	
Article	28481	
Model	FlexBalance Plus F	
Capacity [l]	17.5	
Connection	DN	65
	D [mm]	76.1
Capacity [kW] *	180 - 330	
Flow in the system [m <sup>3</sup> /h]	10 - 17	
K <sub>v</sub> ** [m <sup>3</sup> /h] (ΔP = 1 bar)	131	
Weight [kg]	30	



#### Packaging info

Unity of use	1 Piece
Packaging form	Crate
Packaging dimensions (H. x W. x L.)	360 x 450 x 1140 mm
Weight	43.5 Kilogram



### Classification General Data

<b>Etim Group</b>	Distributors/collectors
<b>Etim Class</b>	Open CH distributor
<b>Product Name</b>	Flexbalance hydraulic separator Plus 65F
<b>Brand</b>	Flamco
<b>Product Series</b>	Flexbalance Plus 50-200 R
<b>Product Type</b>	65

### Attributes

<b>Material</b>	Steel
<b>Surface protection</b>	Powder coating
<b>Max. heating power [kW]</b>	330
<b>Number of boiler connections</b>	2
<b>Boiler connection model</b>	Flange
<b>Nominal inner diameter, boiler connections</b>	DN 65
<b>Installation side connection model</b>	Flange
<b>Nominal inner diameter, installation side</b>	DN 65
<b>Nominal inner diameter, shunt pipe</b>	Not applicable
<b>Number of air-release connections</b>	1
<b>Nominal inner diameter, air-release</b>	1/2" inside

Type	Dimensions					
	A [mm]	B [mm]	C [mm]	E [mm]	H [mm]	I [mm]
<b>FlexBalance Plus F 50</b>	400	350	950	88	154	
<b>FlexBalance Plus F 65</b>	400	350	950	88	154	
<b>FlexBalance Plus F 80</b>	625	470	1265	135	188	
<b>FlexBalance Plus F 100</b>	625	470	1265	135	188	
<b>FlexBalance Plus F 125</b>	830	635	1767	180	213	
<b>FlexBalance Plus F 150</b>	1040	774	2175	225	237	645
<b>FlexBalance Plus F 200</b>	1400	1000	2895	300	277	825
<b>FlexBalance Plus F 250</b>	1850	1220	3646	400	325	977
<b>FlexBalance Plus F 300</b>	1850	1220	3646	400	369	977

Flamco Group  
 Amersfoortseweg 9  
 3751 LJ, Bunschoten - nl  
**T** +31 33 299 75 00  
**F** +31 33 298 64 45  
**E** [info@flamcogroup.com](mailto:info@flamcogroup.com)  
**I** [flamcogroup.com](http://flamcogroup.com)