


**Product Data Sheet (2018-09-17)**
**18261 - Flamco Storage vessel PS-K 750L**


|              |                                 |      |
|--------------|---------------------------------|------|
| Description  | Flamco Storage vessel PS-K 750L |      |
| Article      | 18261                           |      |
| Model        | PS-K 500 - 3000                 |      |
| Capacity [l] | 750                             |      |
| Dimensions * | Ø [mm]                          | 750  |
|              | H [mm]                          | 1970 |
|              | Tilting height [mm]             | 2000 |
| Weight [kg]  | 168                             |      |


**Packaging info**

|                                     |                     |
|-------------------------------------|---------------------|
| Unity of use                        | 1 Piece             |
| Packaging form                      | Pallet              |
| Packaging dimensions (H. x W. x L.) | 2100 x 800 x 940 mm |
| Weight                              | 185 Kilogram        |

### Classification General Data

|                       |                                 |
|-----------------------|---------------------------------|
| <b>Etim Group</b>     | Storage tanks/vessels           |
| <b>Etim Class</b>     | Storage tank                    |
| <b>Product Name</b>   | Flamco Storage vessel PS-K 750L |
| <b>Brand</b>          | Flamco                          |
| <b>Product Series</b> | PSK                             |
| <b>Product Type</b>   | 750                             |

### Attributes

|  |                |
|--|----------------|
| <b>Suitable for central heating</b>                | No             |
| <b>Suitable for heat pump</b>                      | No             |
| <b>Suitable for cooling water installation</b>     | Yes            |
| <b>Mounting method</b>                             | Floor standing |
| <b>Tank material</b>                               | Steel          |
| <b>Surface protection on the inside</b>            | Untreated      |
| <b>Surface protection on the outside</b>           | Coated         |
| <b>Surface material</b>                            | Not applicable |
| <b>With insulation</b>                             | No             |
| <b>Volume [l]</b>                                  | 750            |
| <b>Height [mm]</b>                                 | 1970           |
| <b>Diameter [mm]</b>                               | 750            |
| <b>Diameter without insulation [mm]</b>            | 750            |
| <b>Max. operating pressure [bar]</b>               | 6              |
| <b>Max. temperature [°C]</b>                       | 50             |
| <b>Connection 1</b>                                | Flange         |
| <b>Connection size 1</b>                           | Other          |
| <b>Connection 2</b>                                | Flange         |
| <b>Connection size 2</b>                           | Other          |
| <b>With immersion tube</b>                         | No             |
| <b>With electrical element</b>                     | No             |
| <b>With temperature sensor connection</b>          | Yes            |
| <b>Number of connections of temperature sensor</b> | 3              |
| <b>Connection size temperature sensor</b>          | 1/2 inch       |

| Type      | System connections | DN  | Distance between floor and connections |        |        |
|-----------|--------------------|-----|--|--------|--------|
|           |                    |     | A [mm]                                 | B [mm] | C [mm] |
| PS-K 500  | 4                  | 80  | 315                                    | 810    | 1305   |
| PS-K 750  | 4                  | 100 | 360                                    | 970    | 1580   |
| PS-K 1000 | 4                  | 125 | 385                                    | 1100   | 1815   |
| PS-K 1500 | 4                  | 150 | 460                                    | 1165   | 1870   |
| PS-K 2000 | 4                  | 200 | 500                                    | 1175   | 1850   |
| PS-K 2500 | 4                  | 200 | 520                                    | 1320   | 2120   |
| PS-K 3000 | 4                  | 200 | 640                                    | 1440   | 2240   |

Flamco Group  
Amersfoortseweg 9  
3751 LJ, Bunschoten - nl  
**T** +31 33 299 75 00  
**F** +31 33 298 64 45  
**E** [info@flamcogroup.com](mailto:info@flamcogroup.com)  
**I** [flamcogroup.com](http://flamcogroup.com)